

# 线缆斗

铲斗 0-40 吨

## Cable bucket when you need to be surgical

Steelwrist cable bucket is high from cutting edge to attachment bracket which allows you to properly enter the trench without interferences with the tiltrotator. To avoid problems the tiltrotator gripper unit has extremely robust cylinders protection.

On the larger buckets (S60 and upwards) oversized pipes are used to increase the stiffness of the buckets, while the sheet metal truss structure used on the smaller buckets keep the weight down.



## 技术参数

线缆斗	挖机重量	支架 S-type	宽度 [mm]	斗容 [l]	重量 [kg]	齿 CAT-J	文章
CB1	0-2	S30	240	25	25	-	101154
CB2	1-3	S30	290	30	30	-	101156
CB2T	1-3	S40	290	30	40	J200x3	101155
CB3	2-5	S40	300	5030	5540	-	101157
CB3C	2-4	S40	400/200	50	60	-	101158
CB5	4-6	S40	300	60	70	-	101160
CB5	4-6	S40	400	90	80	-	101162
CB5	4-6	S40	450	100	85	-	101163
CB5T	4-6	S40	300	60	75	J200x3	101161
CB5T	4-6	S40	450	100	95	J200x3	110164
CB6	5-8	S40	400	100	95	-	101165
CB6C	5-8	S40	380/300	80	90	-	101304
CB6	5-8	S45	400	100	110	-	101169
CB6C	5-8	S45	380/300	80	100	-	101168
CB6	5-8	S50	400	100	110	-	101170
CB6	5-8	S50	450	110	115	-	101171
CB6C	5-8	S50	380/300	80	100	-	101166
CB6T	5-8	S50	450	110	120	J200x4	101172
CB6CT	5-8	S50	380/300	80	110	J200x3	101167
CB9	8-12	S45	400	120	135	-	101175
CB9	8-12	S50	400	120	140	-	101176
CB9C	8-12	S50	400/200	80	120	-	101179
CB12	11-13	S45	400	150	210	-	101181
CB12	11-13	S50	400	150	210	-	101183
CB12	11-13	S60	400	150	230	-	101305
CB12T	11-13	S50	400	150	225	J250x2	101182
CB15	11-13	S60	500	230	330	-	101185
CB15C	13-16	S60	480/300	140	265	-	101186
CB15T	13-16	S60	500	230	365	J300x3	101184

线缆斗	挖机重量	支架 S-type	宽度 [mm]	斗容 [m <sup>3</sup> ]	重量 [kg]	齿 CAT-J	文章
CB17	16-18	S60	550	270	370	-	101188
CB17	16-18	S65	550	270	385	-	101189
CB20	18-22	S70	650	430	610	-	101190
CB25	22-26	S70	650	430	610	-	101191
CB30	25-40	S70	800	590	790	-	101193
CB30	25-40	S70/55	800	590	790	-	101356
CB30	25-40	S80	800	590	840	-	101194