

Multigripar

Hydrauliska redskap 0-26 ton



A versatile and strong grapple for general construction tasks

Steelwrist multi grapple is excellent for use in general construction, heavy lifting, stone laying, sorting, timber loading, waste wood handling and light demolition. It is light in weight but still strong, and has a compact design.

Perfect for use with a tiltrotator

Steelwrist grapples are optimized for use with a tiltrotator. The tiltrotator enables you to tilt and rotate your work tool, making it easier to reach awkward angles and work in confined spaces, with more precise control over the handling of materials. This is very practical in tasks where accuracy is crucial, such as sorting and placing objects in areas where space is limited. The need for frequent repositioning of the excavator is reduced. The bracket has a 6 degree angle for level alignment with the tiltrotator rotation plane.

Compact and versatile grapple with impressive grip width

The multi grapple has a construction with Hardox 500 wear plates for unmatched lightness and strength. It has a large grip width and the fully closing by-passing arms ensure even the thinnest objects are gripped securely. The enhanced synchronized arm movements result in smoother operation and precision handling of the objects. The hydraulic design is safe and robust with shock relief- and load holding valves.

Modular design for upgrade to SQ/Open-S

The grapple is available with an interface following the symmetrical standard (S standard), which is the fastest growing standard internationally. Thanks to the modular design it is possible to upgrade the grapple from S-type (from S50) to SQ-type. Steelwrist SQ is our high performing automatic oil connection technology used to easily change and connect hydraulic work tools on the excavator. Naturally all SQ products comply with the Open-S standard.



Teknisk specifikation

Modell	MGX2	MGX8	MGX14	MGX20	MGX26
Fäste	S30	S40, S45, SQ45, S50, SQ50	S45, SQ45, S50, SQ50, S60, SQ60	S60, SQ60	S70, SQ70
Maskinvikt [ton]	0-2	3-8	6-14	12-20	18-26
Max brytmoment [kNm]	28	70	80	180	240
Vikt från [kg]	53	199	307	488	605
Bredd [mm]	258	539	599	677	747
Längd [mm]	665	854	959	1084	1189
Höjd [mm]	402	450	508	567	616
Höjd, max öppen [mm]	575	643	721	808	883
Höjd, spets mot spets [mm]	635	759	857	956	1045
Gripvidd [mm]	1066	1437	1609	1819	2028
Gripvidd, minsta objekt [mm]	82	98	107	119	135
Gripkraft, spets, mot spets [kN]	6,5	10	17	21	25
Griparea [m2]	0,12	0,22	0,27	0,36	0,45
Lyftkapacitet [kg]	1000	3000	6000	8000	10000
Oljeflöde [l/min]	12	26	46	66	90
Max tryck [bar]	250	250	250	250	250