

S30/180

퀵 링크 0-2 톤

프론트핀훅 안전장치 장착된 주강 전용링크

The S30 quick coupler is used to connect and disconnect work tools for compact excavators. It follows the symmetrical standard and has either a mechanical snap-in locking function (semi-automatic) or hydraulic locking function (automatic).

The S30 quick coupler is casted in one piece, has large work tool pin contact surfaces and optimized design, making it lightweight but yet robust which will ensure a long life time. The coupler has a fully closed design to reduce any risk of debris entering the locking mechanism.

The quick coupler is equipped with safety hooks that secure the work tools front shaft to reduce the risk of dropping the work tool if by mistake it is not connected correctly. We call this safety technology Front Pin Hook (FPH). The quick coupler complies with all relevant safety regulations such as EN474-5 and ISO 13031:2023.





Our expander pin technology ensures a play free connection to reduce wear and extend the life of your equipment.

측정		
형식	S30/180	
몸체높이 (미리 미터)	82	
무게 (키로그램)	15	
폭 (미리미터)	180	
길이 (미리미터)	230	
핀 직경 (미리미 터)	25-35	
암끝단 최고폭 너비 (미리미터)	125	
핀간거리, 중심 간 측정 (미리미 터)	85-150	
	C-C Building Height	Max width dipper arm Width

기술자 시방서		
형식	S30/180	
권하는 장비 무 게 (톤)	0-2	
吊 钩,选配 (톤)	0,75	
Front Pin Hook	예	
몸체	이빨 옵션	

STEELWRIST AB www.steelwrist.com info@steelwrist.com

