

## S70

## 液压快换 18-33 吨

Steelwrist symmetrical quick couplers are unique. No other manufacturer cast the entire quick coupler in steel and includes front pin locking as standard for maximum safety. We also include Expander pins so that we create a truss structure taking up the lateral forces that comes when you start using a tiltrotator.

The advantage of casting in steel is that materials can be optimized where needed (for example, contact surfaces to pins in order to minimize the preassure per square mm) and eliminate material where it is not needed. The result is an unrivaled relation between strength and weight.

With Front Pin Lock you are safe during tool changes regardless of control system, the size and age of your excavator. A simple mechanical solution that protects against the most common risk, i e that you by misstake connect the rear pin in the wrong way without noticing it. Read more about the Front Pin Lock here.



Unlike traditional solutions that only indicates that the lock is open (or

modern sensor-based solutions that indicates when you are not connected correctly), Steelwrist Front Pin Lock solves both problems. We indicate red when the lock is open and green when the bucket is in a secured position. In addition, we ensure that you do not drop a bucket even if you made a mistake in the coupling process. As long as you have the front pin in the front jaw (the one that you see from the cabin) then you are safe even if you locked above the rear pin. In a way, one can say that our solution is both a "warning" and an "airbag" when our competitors a "warning light".

尺寸		
类型	S70	S70wide
高度(毫米)	200	200
重量(公斤)	273	260
宽度(毫米)	450	450
长度(毫米)	600	600
小臂前端销子直 径(毫米)	60-90	70-90
小臂宽度(毫 米)	320-412	350-431
销距 (铲斗两销 子中心距( 毫 米))	400-520	470-565

技术参数		
类型	S70	S70wide
推荐机器重量 (吨)	18-32	25-33
吊钩(吨)	8	8
前销锁止止	是的	是的
身体	铸造	铸造