

Tilt couplers TCX

Tilt- and Rotor Coupler 0-2 tonnes

The TCX tilt coupler – a tilt function for the smallest excavators

The TCX tilt coupler is designed for excavators below two tonnes and offers the user a tilt function and an integrated quick coupler for changing between work tools. TCX is available as Direct mounted with a S30 coupler with either manual snap-on or hydraulic locking.

The fully cast and compact body has a low weight. The fact that the TCX tilt coupler is free from welding, has large pin contact surfaces and optimized material thickness, creates an extremely robust design which will ensure a longer life time.

- Front Pin Hook coupler for safe work tool changes
- Up to 30° tilt angle in each direction
- Optimized range of work tools



🔧 Technical specification

Tilt couplers	TCX
Tilt couplers TCX	S30
Machine weight [ton]	0-2
Max Breakout torque [kNm]	
Weight from [kg]	28
Building height [mm]	162
Length [mm]	
Cylinder width [mm]	
Maximum tilt angle [mm]	±30°
Max width dipper arm [mm]	125
Pin diameter [mm]	25-35
Pin distance [cc-measure] [mm]	85-180
Tilt Torque [kNm]	1,9
Holding Torque [kNm]	1,9
Lifting hook [ton]	0,75
Oil Flow [l/min]	5-10
Max pressure [bar]	
Max Pressure Separate AUX [bar]	175
Safety solution	-