

# XT20

**Tilt Coupler 12-20 tonnes**

---



## When a robust tilt function is enough

The Steelwrist tilt coupler is a combination between a robust tilt motor and the patented Front Pin Lock technology or Front Pin Hook from Steelwrist. With the Steelwrist tilt coupler you will get a safe quick coupler solution when you just need the tilt function and not the full blown tiltrotator functionality. The Steelwrist tilt coupler is based on the steel casted coupler as well as the robust direct fit top with expander pins.



## Teknisk specifikation

Quick coupler	S60	SQ60
Machine weight [lb]	26400-44000	26400-44000
<b>Max Breakout torque [kNm]</b>		
Weight from [lb]	792	836
Building height [inch]	20.28	20.28
<b>Length [inch]</b>		
<b>Cylinder width [inch]</b>		
Max tilt angle [degrees]	±60	±60
Max width dipper arm [inch]	13.15	13.15
Pin diameter [inch]	2.36-3.15	2.36-3.15
Pin distance [cc-measure] [inch]	11.81-18.11	11.81-18.11
Pin distance [cc-measure] [mm]	300-460	300-460
Tilt Torque [kNm]	13,3	13,3
Holding Torque [kNm]	40,7	40,7
Lifting hook [lb]	11000	11000
Oil Flow [gallons/min]	7-21	7-21
<b>Max pressure [bar]</b>		
Max Pressure Separate AUX [bar]	350	350
Safety solution	FPL2	FPL2