

XT23

Tilt Coupler 18-24 tonnes



When a robust tilt function is enough

The Steelwrist tilt coupler is a combination between a robust tilt motor and the patented Front Pin Lock technology or Front Pin Hook from Steelwrist. With the Steelwrist tilt coupler you will get a safe quick coupler solution when you just need the tilt function and not the full blown tiltrotator functionality. The Steelwrist tilt coupler is based on the casted coupler as well as the robust direct fit top with expander pins.



🔑 Teknisk specifikation

| | | |
|----------------------------------|--------------|--------------|
| Quick coupler | S70 | SQ70 |
| Machine weight [ton] | 18-24 | 18-24 |
| Max Breakout torque [kNm] | | |
| Weight from [kg] | 620 | 650 |
| Building height [mm] | 625 | 625 |
| Length [mm] | | |
| Cylinder width [mm] | | |
| Maximum tilt angle [degrees] | ±60 | ±60 |
| Max width dipper arm [mm] | 400 | 400 |
| Pin diameter [mm] | 60-80 | 60-80 |
| Pin distance [cc-measure] [mm] | 270-485 | 270-485 |
| Tilt Torque [kNm] | 17,8 | 17,8 |
| Holding Torque [kNm] | 53,1 | 53,1 |
| Lifting hook [ton] | 8 | 8 |
| Oil Flow [l/min] | 35-105 | 35-105 |
| Max pressure [bar] | | |
| Max Pressure Separate AUX [bar] | 350 | 350 |
| Safety solution | FPL2 | FPL2 |